

FOAMING CARPET STAIN REMO

Version 1.0

Revision Date 03/07/2017

Print Date 12/18/2018

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : FOAMING CARPET STAIN REMO

Material number : CASPOT19

Manufacturer or supplier's details

Company : Zep Inc.

Address : 11627 - 178 Street
Edmonton, Alberta T5S 1N6
Canada

Telephone : 404-352-1680

Emergency telephone numbers**For SDS Information** : Compliance Services 1-877-428-9937**For a Medical Emergency** : 877-541-2016 Toll Free - All Calls Recorded**For a Transportation** : CHEMTREC: 800-424-9300 - All Calls Recorded.**Emergency****Recommended use of the chemical and restrictions on use**

Recommended use : Carpet Care

Note: This product is labeled as a consumer product in accordance with the Canadian Consumer Chemicals and Containers Regulations (CCCR) of Health Canada. The warnings presented below in this Safety Data Sheet (SDS) comply with the WHMIS 2015 Hazardous Products Regulation (GHS - Globally Harmonized System of Classification and Labeling). The requirements for the labeling and warnings of consumer products may differ from those required for GHS based hazard communication.

SECTION 2. HAZARDS IDENTIFICATION**Emergency Overview**

Appearance	Aerosol containing a liquefied gas
Colour	clear
Odour	characteristic

GHS Classification

Gases under pressure : Liquefied gas

Eye irritation : Category 2A

Reproductive toxicity : Category 1B


GHS label elements

FOAMING CARPET STAIN REMO

Version 1.0

Revision Date 03/07/2017

Print Date 12/18/2018

Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	H280 Contains gas under pressure; may explode if heated. H319 Causes serious eye irritation. H360 May damage fertility or the unborn child.
Precautionary statements	:	Prevention: P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P264 Wash skin thoroughly after handling. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. Response: P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308 + P313 IF exposed or concerned: Get medical advice/ attention. P337 + P313 If eye irritation persists: Get medical advice/ attention. Storage: P410 + P403 Protect from sunlight. Store in a well-ventilated place. Disposal: Dispose of contents/container in accordance with local regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components

Chemical name	CAS-No.	Concentration [%]
2-butoxyethanol	111-76-2	>= 5 - < 10
butane	106-97-8	>= 1 - < 5
acetone	67-64-1	>= 1 - < 5
propane	74-98-6	>= 1 - < 5
sodium borate, decahydrate	1303-96-4	>= 0.1 - < 1

SECTION 4. FIRST AID MEASURES

General advice	:	Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	:	If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.

FOAMING CARPET STAIN REMO

Version 1.0

Revision Date 03/07/2017

Print Date 12/18/2018

- In case of skin contact : If skin irritation persists, call a physician.
Wash off immediately with plenty of water for at least 15 minutes.
Remove contaminated clothing and shoes.
Wash contaminated clothing before reuse.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
DO NOT induce vomiting unless directed to do so by a physician or poison control center.
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : Effects are dependent on exposure (dose, concentration, contact time).
Effects are immediate and delayed.
Chronic effects are delayed and symptoms may not be observed during an exposure.
Causes serious eye irritation.
May damage fertility or the unborn child.
Review section 2 of SDS to see all potential hazards.
- Notes to physician : Treat symptomatically. Symptoms may be delayed.
-

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
Water spray jet
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon dioxide (CO₂)
Carbon monoxide
Smoke
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

FOAMING CARPET STAIN REMO

Version 1.0

Revision Date 03/07/2017

Print Date 12/18/2018

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Evaporates.
Evacuate personnel to safe areas.
Remove all sources of ignition.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Sweep up or vacuum up spillage and collect in suitable container for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations.
Always replace cap after use.
Do not breathe vapours or spray mist.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.
No smoking.
Observe label precautions.
Keep in a dry, cool and well-ventilated place.
Electrical installations / working materials must comply with the technological safety standards.

Materials to avoid : Oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type	Control	Basis
------------	---------	------------	---------	-------

SAFETY DATA SHEET



FOAMING CARPET STAIN REMO

Version 1.0

Revision Date 03/07/2017

Print Date 12/18/2018

		(Form of exposure)	parameters / Permissible concentration	
2-butoxyethanol	111-76-2	TWA	20 ppm 97 mg/m ³	CA AB OEL
		TWA	20 ppm	CA BC OEL
		TWAEV	20 ppm 97 mg/m ³	CA QC OEL
		TWA	20 ppm	ACGIH
		TWA	5 ppm 24 mg/m ³	NIOSH REL
		TWA	50 ppm 240 mg/m ³	OSHA Z-1
		TWA	25 ppm 120 mg/m ³	OSHA P0
butane	106-97-8	PEL	20 ppm 97 mg/m ³	CAL PEL
		TWA	1,000 ppm	CA AB OEL
		TWA	600 ppm	CA BC OEL
		STEL	750 ppm	CA BC OEL
acetone	67-64-1	TWAEV	800 ppm 1,900 mg/m ³	CA QC OEL
		TWA	500 ppm 1,200 mg/m ³	CA AB OEL
		STEL	750 ppm 1,800 mg/m ³	CA AB OEL
		TWA	250 ppm	CA BC OEL
		STEL	500 ppm	CA BC OEL
		STEV	1,000 ppm 2,380 mg/m ³	CA QC OEL
		TWAEV	500 ppm 1,190 mg/m ³	CA QC OEL
		TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	250 ppm 590 mg/m ³	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m ³	OSHA Z-1
		TWA	750 ppm 1,800 mg/m ³	OSHA P0
		STEL	1,000 ppm 2,400 mg/m ³	OSHA P0
STEL	750 ppm 1,780 mg/m ³	CAL PEL		
C	3,000 ppm	CAL PEL		
PEL	500 ppm 1,200 mg/m ³	CAL PEL		
propane	74-98-6	TWA	1,000 ppm	CA AB OEL
		TWA	1,000 ppm	CA BC OEL
		TWAEV	1,000 ppm 1,800 mg/m ³	CA QC OEL
		TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,800 mg/m ³	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m ³	OSHA Z-1

SAFETY DATA SHEET



FOAMING CARPET STAIN REMO

Version 1.0

Revision Date 03/07/2017

Print Date 12/18/2018

		TWA	1,000 ppm 1,800 mg/m3	OSHA P0
		PEL	1,000 ppm 1,800 mg/m3	CAL PEL
sodium borate, decahydrate	1303-96-4	TWA	1 mg/m3	CA AB OEL
		STEL	3 ppm	CA AB OEL
		TWAEV	5 mg/m3	CA QC OEL

Biological occupational exposure limits

Component	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
2-BUTOXYETHANOL	111-76-2	Butoxyacetic acid (BAA)	Urine	End of shift (As soon as possible after exposure ceases)	200.mg/g Creatinine	ACGIH BEI
2-PROPANONE	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material

Remarks

: Protective gloves

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Safety glasses

Eye wash bottle with pure water

Skin and body protection

: Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures

: When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

: Aerosol containing a liquefied gas

FOAMING CARPET STAIN REMO

Version 1.0

Revision Date 03/07/2017

Print Date 12/18/2018

Colour	: clear
Odour	: characteristic
Odour Threshold	: No data available
pH	: 9 - 10
Melting point/freezing point	: No data available
Boiling point	: 100 °C
Flash point	: No data available
Evaporation rate	: No data available
Flammability (solid, gas)	: The product is not flammable.
Upper explosion limit	: Not applicable
Lower explosion limit	: Not applicable
Vapour pressure	: No data available
Density	: 0.9922 g/cm ³
Solubility(ies)	
Water solubility	: soluble
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: not determined
Thermal decomposition	: No data available
Viscosity	
Viscosity, kinematic	: No data available
Heat of combustion	: 7.7 kJ/g

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air. No decomposition if stored and applied as directed.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: Carbon oxides

FOAMING CARPET STAIN REMO

Version 1.0

Revision Date 03/07/2017

Print Date 12/18/2018

SECTION 11. TOXICOLOGICAL INFORMATION
Potential Health Effects

Aggravated Medical Condition : None known.

Symptoms of Overexposure : Effects are dependent on exposure (dose, concentration, contact time).
Effects are immediate and delayed.
Chronic effects are delayed and symptoms may not be observed during an exposure.

Carcinogenicity:
IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH

Confirmed animal carcinogen with unknown relevance to humans

2-butoxyethanol

111-76-2

Acute toxicity
Product:

Acute oral toxicity : Acute toxicity estimate : 4,556 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : > 10 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Components:
butane:

Acute inhalation toxicity : LC50 Mouse: 1,237 mg/l
Exposure time: 2 h

LC50 Rat: 1,355 mg/l

acetone:

Acute oral toxicity : LD50 Rat: 5,800 mg/kg

Acute inhalation toxicity : LC50 Rat: 132 mg/l
Exposure time: 3 h

FOAMING CARPET STAIN REMO

Version 1.0

Revision Date 03/07/2017

Print Date 12/18/2018

LC50 Rat: 50.1 mg/l

Acute dermal toxicity : LD50 Guinea pig: > 7,426 mg/kg

LD50 Rabbit: > 7,426 mg/kg

propane:

Acute inhalation toxicity : LC50 Mouse: 1,237 mg/l
Exposure time: 2 h

LC50 Rat: 658 mg/l
Exposure time: 4 h

LC50 Rat: 1,355 mg/l

Skin corrosion/irritation

Product:

Remarks: May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation

Product:

Remarks: Severe eye irritation

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

2-butoxyethanol:

butane:

acetone:

propane:

sodium borate, decahydrate:

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

FOAMING CARPET STAIN REMO

Version 1.0

Revision Date 03/07/2017

Print Date 12/18/2018

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Product:

Partition coefficient: n-octanol/water : Remarks: No data available

Components:

butane :

Partition coefficient: n-octanol/water : Pow: 2.89

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

SAFETY DATA SHEET



FOAMING CARPET STAIN REMO

Version 1.0

Revision Date 03/07/2017

Print Date 12/18/2018

Transportation Regulation (TDG) / Règlement Pour Le Transport (TMD): (Canada):
UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IMDG (Vessel):
UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IATA (Cargo Air):
UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IATA (Passenger Air):
UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: 49 CFR (USA):
UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under Transport Dangerous Goods (TDG) Canada regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

This product has been classified according to the hazard criteria of the HPR and the SDS contains all of the information required by the HPR.

The components of this product are reported in the following inventories:

TSCA

On TSCA Inventory

DSL

All components of this product are on the Canadian DSL

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

WHMIS - GHS Label Information:

Hazard pictograms



FOAMING CARPET STAIN REMO

Version 1.0

Revision Date 03/07/2017

Print Date 12/18/2018

Signal word	:	Danger:
Hazard statements	:	Contains gas under pressure; may explode if heated. Causes serious eye irritation. May damage fertility or the unborn child.
Precautionary statements	:	<p>Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wash skin thoroughly after handling. Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>Response: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention.</p> <p>Storage: Protect from sunlight. Store in a well-ventilated place.</p> <p>Disposal: Dispose of contents/container in accordance with local regulation.</p>

Version:	1.0
Revision Date:	03/07/2017
Print Date:	12/18/2018

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®, Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®, Rexodan®, Mykal™, and a number of private labeled brands.